



TABLE OF CONTENTS



MINIATURE

Mini fuses in five sizes to 20 Amps.

- Slow Blow
- Medium Blow
- Fast Blow
- Super Fast Blow

Fuses **4-5**



DIAZED

"Bottle" fuses in five sizes to 200 Amps.

- gL/gG - Slow Blow
- - Fast Blow
- gR - Semiconductor Protection

Fuses **6-7**
Accessories **10-11**



NEOZED

Compact fuses in three sizes to 100 Amps.

- gL/gG - Slow Blow
- gR - Semiconductor Protection

Fuses **8-9**
Accessories **10-11**



CYLINDER

Standard cylinder fuses are available in four sizes to 125 Amps, with or without blown fuse Indicator Pins.

- gL/gF - Line Protection
- aM - Motor Protection
- gR - Semiconductor Protection

Cylinder Bolt fuses are available in two diameters with multiple fixing centers.

- gR - Semiconductor Protection

Fuses - Standard **12-13**
Fuses - Bolt **14**
Accessories **15**



NH

Knife Blade or Stud Mount designs in six sizes with current ratings of 2 to 1600 Amps.

- gL/gG - Line Protection
- aM - Motor Protection
- gR/aR - Semiconductor Protection

Fuses **16-21**
Accessories **19**



ITALIAN

Cylinder style fuses available in four sizes with current ratings from 2 to 100 Amps.

- gL - Line Protection

Fuses **22**



BRITISH

British Line Protection fuses are available with four mounting plate designs with current ratings from 2 to 63 Amps.

- gG - Line Protection
- British Semiconductor fuses are available in single and double body units with multiple diameters and fixing centers.

- aR - Semiconductor Protection

Fuses - Line **23**
Fuses - Semi. **24-25**



SQUARE BODY

Square body fuses for semiconductor devices to 1000 Amps.

- aR - Semiconductor Protection

Fuses **26-31**
Accessories **19**



HIGH VOLTAGE

Fuses for distribution circuits in four sizes to 36KV.

Fuses **32-33**



ACCESSORIES

- Screw Caps
- Adapter Screws and Rings
- Fuse Base Covers
- Fuse Bases
- Tools
- End Plates
- Microswitches
- Terminal Covers
- Fuse Handles

10-11, 15, 19

Siemens Cross Reference **34-35**

MINIATURE

Miniature Fuses are typically used to protect electronic devices, laboratory and measurement instruments, stereos, TV's, VCR's etc. They are available in four sizes with a current range of 20mA to 20 Amps.

Miniature Fuses are manufactured according to VDE 0820 part 1, VDE 0820 part 2, IEC publication 127, CEE publication 4 and actual DIN standards.

Slow

Typical Marking: "T"

Medium

Typical Marking: "M"

Fast

Typical Marking: "F"

Super Fast

Typical Marking: "FF"



5 x 20



USA
upon request



5 x 25

Ordering Information

Voltage 250V
DIN 41662
IEC-127-2/III

DIN 41571-2
Cat. No.

DIN 41661
IEC-127-2/II

Voltage 250V
DIN 41571-2

Cat. No.

Current

Slow Medium Fast Super Fast

Medium

20mA
32mA
40mA
50mA
63mA
80mA
100mA
125mA
160mA
200mA
250mA
315mA

		0.02M5x20M 0.032M5x20M		
	0.05M5x20T ⁴	0.05M5x20M	0.05M5x20F ⁴	
	0.08M5x20T ⁴	0.08M5x20M		
	0.1M5x20T ⁴	0.1M5x20M	0.1M5x20F ⁴	
	0.125M5x20T ⁴	0.125M5x20M	0.125M5x20F ⁴	0.125M5x20FF ⁴
	0.16M5x20T ⁴	0.16M5x20M	0.16M5x20F ⁴	0.16M5x20FF ⁴
	0.2M5x20T ⁴	0.2M5x20M	0.2M5x20F ⁴	0.2M5x20FF ⁴
	0.25M5x20T ⁴	0.25M5x20M	0.25M5x20F ⁴	0.25M5x20FF ⁴
	0.315M5x20T ⁴	0.315M5x20M	0.315M5x20F ⁴	0.315M5x20FF ⁴

0.032M5x25M
0.04M5x25M
0.05M5x25M
0.063M5x25M
0.08M5x25M
0.1M5x25M
0.125M5x25M
0.16M5x25M
0.2M5x25M
0.25M5x25M
0.315M5x25M

400mA
500mA
630mA
700mA
800mA
1.0A
1.25A
1.4A
1.6A
2.0A
2.5A

	0.4M5x20T ⁴	0.4M5x20M	0.4M5x20F ⁴	0.4M5x20FF ⁴
	0.5M5x20T ⁴	0.5M5x20M	0.5M5x20F ⁴	0.5M5x20FF ⁴
	0.63M5x20T ⁴	0.63M5x20M	0.63M5x20F ⁴	0.63M5x20FF ⁴
	0.7M5x20T	0.7M5x20M	0.7M5x20F	
	0.8M5x20T ⁴	0.8M5x20M	0.8M5x20F ⁴	0.8M5x20FF ⁴
	1.0M5x20T ⁴	1.0M5x20M	1.0M5x20F ⁴	1.0M5x20FF ⁴
	1.25M5x20T ⁴	1.25M5x20M	1.25M5x20F ⁴	1.25M5x20FF ⁴
	1.4M5x20T	1.4M5x20M		
	1.6M5x20T ⁴	1.6M5x20M	1.6M5x20F ⁴	1.6M5x20FF ⁴
	2.0M5x20T ⁴	2.0M5x20M	2.0M5x20F ⁴	2.0M5x20FF ⁴
	2.5M5x20T ⁴	2.5M5x20M	2.5M5x20F ⁴	2.5M5x20FF ⁴

0.4M5x25M
0.5M5x25M
0.63M5x25M

0.8M5x25M
1.0M5x25M
1.25M5x25M

1.6M5x25M
2.0M5x25M
2.5M5x25M

3.15A
4.0A
5.0A
6.3A
7.0A
8.0A
10.0A
12.5A
16.0A
20.0A

	3.15M5x20T ⁴	3.15M5x20M	3.15M5x20F ⁴	3.15M5x20FF ⁴
	4.0M5x20T ⁴	4.0M5x20M	4.0M5x20F ⁴	4.0M5x20FF ⁴
	5.0M5x20T ⁴	5.0M5x20M	5.0M5x20F ⁴	5.0M5x20FF ⁴
	6.3M5x20T ⁴	6.3M5x20M	6.3M5x20F ⁴	6.3M5x20FF ⁴
	8.0M5x20T*	8.0M5x20M	8.0M5x20F*	8.0M5x20FF ⁴
	10.0M5x20T*	10.0M5x20M	10.0M5x20F*	10.0M5x20FF ⁴
	12.5M5x20T*	12.5M5x20M*	12.5M5x20F*	12.5M5x20FF ⁴
	16.0M5x20T*	16.0M5x20M*	16.0M5x20F*	
	20.0M5x20T*	20.0M5x20M*	20.0M5x20F*	

3.15M5x25M
4.0M5x25M
5.0M5x25M
6.3M5x25M

8.0M5x25M *
10.0M5x25M *



16.0M5x25M *

Std. Pk. 10

Std. Pk. 10

All fuses listed are low breaking capacity. For high breaking capacity fuses please contact Altech.

* Not standard rating.
¹ Rated Voltage 500V.
² Rated Voltage 150V.
³ Rated Voltage 60V.
⁴ UL recognized version available upon request.
⁵ UL rated at 700V.





5 x 25
with Indicator

Voltage 250V
DIN 41576-1, -2

Cat. No.

Medium Fast

0.08M5x25M/I
0.1M5x25M/I
0.125M5x25M/I
0.16M5x25M/I
0.2M5x25M/I
0.25M5x25M/I
0.315M5x25M/I

0.4M5x25M/I
0.5M5x25M/I
0.63M5x25M/I


0.8M5x25M/I
1.0M5x25M/I
1.25M5x25M/I

1.6M5x25M/I 1.6M5x25F/I
2.0M5x25M/I 2.0M5x25F/I
2.5M5x25M/I 2.5M5x25F/I

3.15M5x25M/I 3.15M5x25F/I
4.0M5x25M/I 4.0M5x25F/I
5.0M5x25M/I 5.0M5x25F/I
6.3M5x25M/I 6.3M5x25F/I

8.0M5x25M/I* 8.0M5x25F/I*
10.0M5x25M/I* 10.0M5x25F/I*

Std. Pk. 10



5 x 30

Voltage 500V
DIN 41571-2

Cat. No.

Medium

0.032M5x30M
0.04M5x30M
0.05M5x30M
0.063M5x30M
0.08M5x30M
0.1M5x30M
0.125M5x30M
0.16M5x30M
0.2M5x30M
0.25M5x30M
0.315M5x30M

0.4M5x30M
0.5M5x30M
0.63M5x30M

0.8M5x30M
1.0M5x30M
1.25M5x30M


1.6M5x30M
2.0M5x30M
2.5M5x30M

3.15M5x30M
4.0M5x30M
5.0M5x30M
6.3M5x30M

8.0M5x30M*
10.0M5x30M*

16.0M5x30M*

Std. Pk. 10



6.3 x 32

Voltage 250V

Cat. No.

Slow Fast Super Fast

0.032M6.3x32T⁴
0.04M6.3x32T⁴
0.05M6.3x32T⁴
0.063M6.3x32T⁴
0.08M6.3x32T⁴
0.1M6.3x32T⁴
0.125M6.3x32T⁴
0.16M6.3x32T⁴
0.2M6.3x32T⁴
0.25M6.3x32T⁴
0.315M6.3x32T⁴

0.05M6.3x32F
0.063M6.3x32F
0.08M6.3x32F
0.1M6.3x32F
0.125M6.3x32F
0.16M6.3x32F
0.2M6.3x32F
0.25M6.3x32F
0.315M6.3x32F

0.16M6.3x32FF^{1,4,5}
0.2M6.3x32FF^{1,4,5}
0.25M6.3x32FF^{1,4,5}
0.315M6.3x32FF^{1,4,5}

0.4M6.3x32T⁴
0.5M6.3x32T⁴
0.63M6.3x32T⁴
0.7M6.3x32T
0.8M6.3x32T⁴
1.0M6.3x32T⁴
1.25M6.3x32T⁴

0.4M6.3x32F
0.5M6.3x32F
0.63M6.3x32F
0.7M6.3x32F
0.8M6.3x32F
1.0M6.3x32F⁴
1.25M6.3x32F⁴

0.4M6.3x32FF^{1,4,5}
0.5M6.3x32FF^{1,4,5}
0.63M6.3x32FF^{1,4,5}
0.8M6.3x32FF^{1,4,5}
1.0M6.3x32FF^{1,4,5}
1.25M6.3x32FF^{1,4,5}

1.6M6.3x32T⁴
2.0M6.3x32T⁴
2.5M6.3x32T⁴

1.6M6.3x32F⁴
2.0M6.3x32F⁴
2.5M6.3x32F^{2,4}

1.6M6.3x32FF^{1,4,5}
2.0M6.3x32FF^{1,4,5}
2.5M6.3x32FF^{1,4}

3.15M6.3x32T⁴
4.0M6.3x32T⁴
5.0M6.3x32T⁴
6.3M6.3x32T⁴
7.0M6.3x32T
8.0M6.3x32T
10.0M6.3x32T
12.5M6.3x32T
16.0M6.3x32T
20.0M6.3x32T

3.15M6.3x32F^{2,4}
4.0M6.3x32F^{2,4}
5.0M6.3x32F^{3,4}
6.3M6.3x32F^{3,4}
7.0M6.3x32F³
8.0M6.3x32F³
10.0M6.3x32F³
12.5M6.3x32F³
16.0M6.3x32F³
20.0M6.3x32F³

3.15M6.3x32FF^{1,4}
4.0M6.3x32FF^{1,4}
5.0M6.3x32FF^{1,4}
6.3M6.3x32FF^{1,4}
8.0M6.3x32FF^{1,4}
10.0M6.3x32FF^{1,4}
12.5M6.3x32FF^{1,4}
16.0M6.3x32FF^{1,4}
20.0M6.3x32FF^{1,4}

Std. Pk. 10

